

RocketPort® INFINITY and EXPRESS

16-Port Surge Interface

Part Number: 30035-9



KEY FEATURES AND BENEFITS

- 15KV Surge Protection
- DB9 Male connectors
- RS-232/422/485 software-selectable ports
- Communications speeds up to 460Kbps
- RoHS2 compliant under CE

PRODUCT DESCRIPTION

Flexible, reliable and high-speed serial port expansion.

The next generation RocketPort 16-Port Surge Interface has 16 DB9M connections that can be configured for RS-232/422/485 serial communications at speeds up to 460Kbps. The surge interface provides 25KV surge protection on the serial ports. The interface

also contains an additional connection for the host interface cable. This product is not usable with older RocketPort ISA, PCI, or uPCI products, and is only suitable for use with the RocketPort INFINITY PCI-X and RocketPort EXPRESS PCIe products.



ROCKETPORT SPECIFICATIONS

HARDWARE

Dimensions Product Weight 7.5" x 5.5" x 0.9" 23.3 oz

ELECTRICAL SPECIFICATIONS

Surge Protection 25KV @400A for 1ns

ENVIRONMENTAL SPECIFICATIONS

Air Temperature System On

0° to 60°C System Off
Operating Humidity -20° to 85°C 5% to 95% 0 to 10,000 feet Mean time between failures (MTBF) 31.4 years

SERIAL COMMUNICATIONS

(16) DB9M RS-232/422/485 Port Communication Software Interfaces Baud Rate 460Kbps

FEATURES

RoHS 2 compliant under CE Rugged metal housing Easy Setup 5 Year Warranty

REGULATORY APPROVALS

Emissions

Canadian EMC Requirements ICES-003 European Standard EN55022 FCC Part 15 Subpart B: Class A limit AS/NZS CISPR 22

Immunity

European Standard EN55024 IEC 1000-4-2/EN61000-4-2: ESD IEC 1000-4-3/EN61000-4-3: RF

IEC 1000-4-4/EN61000-4-4: Fast Transient IEC 1000-4-5/EN61000-4-5: Surge IEC 1000-4-6/EN61000-4-6: Conducted

Disturbance

IEC 1000-4-8/EN61000-4-8: Magnetic Field IEC 1000-4-11/EN61000-4-11: Dip and Voltage


IEC 60950/EN60950 (LISTED) CSA C22.2 No. 60950/UL60950 Third Edition

Other

RoHS2 Compliant

Regulatory Approvals ✓ROHS (FC CUL)US

PINOUTS GND 4 DTR 8 8 CTS RxD+ 3 TxD TxD-(7) **(Z**) TxD+ RTS 2 RxD-2 RxD • (6) DSR CD • \bigcirc RS-422 RS-232 0 0 GND • (8) RxD+ -(3) TxD-(7) (7) TxD+ 2 RS-485 Full Duplex RS-485 Half Duplex





Warranty Information

Comtrol offers a 30-day satisfaction guarantee and 5-year limited warranty.

Sales Support

+1.763.957.6000 sales@comtrol.com

Technical Support

+1.763.957.6000 www.comtrol.com/support

Email, FTP, and Web Support

info@comtrol.com ftp.comtrol.com www.comtrol.com